GRASSPAVE2 & GRAVELPAVE2 - BASE COURSE DEPTH RECOMMENDATIONS



	No colt of the color of the col					
	Normal Traffic		Occassional Passes		Infrequent Passes	
	CBR 2-4	CBR >4	CBR 2-4	CBR >4	CBR 2-4	CBR >4
Heavy Fire Truck & H-20 Loading						
Max 110 psi	14 in	12-14 in	12-14 in	12 in	12 in	10-12 in
80000 lb						
0000015						
Light Fire Truck & H-15 Loading						
Typical 85 psi	12 in	10-12 in	10 in	8-10 in	8-10 in	8 in
60,000 lb	12	10 12 111	10 111	0 10 111	0 10 111	0
00,000 10						
Hilitar 9. Dolivom, Truck 9. H. 10. Londing						
Utility & Delivery Truck & H-10 Loading	0.40:	0 .	0.40:	.	c 0 :	<i>c</i> .
Typical 60 psi	8-10 in	8 in	8-10 in	6-8 in	6-8 in	6 in
40,000 lb						
Cars & Pick-Up Truck Access						
Typical 45 psi	6-8 in	6 in	6 in	4-6 in	4-6 in	2-4 in
8,000 lb						
-,						
Trail Use and Cart Paths						
<1,000 lb	6 in	4-6 in	2-4 in	0-2 in	None	None
1-7-5-5-12	J	' ' ' '		J =	110110	110110

^{*} THESE DEPTH RECOMMENDATIONS SHOULD BE VERIFIED BY THE PROJECT ENGINEER AND LOCAL AUTHORITIES

