

Information deemed reliable, but not guaranteed.

**Plastic Pavers**

**Concrete Pavers**

Feature	Grasspave2	Geoblock	Tuff Track	EcoRain	AirPave	EZ Roll	Grassy Pavers	Grass-Cel	Checker Block	Grasscrete
<b>Hydrogrow</b>	Yes	NO	NO	NO	NO	NO	NO	NO	NO	NO
<b>Paver Material</b>	<b>100% Recycled HDPE</b>	Up to 97% Recycled HDPE	50% Recycled HDPE	100% Recycled PP	PP/HDPE	Up to 100% Recycled PP/HDPE	97% Recycled HDPE	5% Recycled HDP	PC Concrete	CIP Concrete
<b>Standard Size</b>	<b>6.6 ft x 65.6 ft x 1 inch</b>	1.64' x 3.28' x 2"	2' x 2' x 1.5"	1.64' x 1' x 2"	31.8" x 31.9" x 1"	24' x 24' x 1.25"	9.75" x 15" x 1.75"	13" x 12.5" x 1.5"	2' x 2' x 4"	4" to 6" thick**
<b>Weight (lbs per sq. ft.)</b>	<b>0.42</b>	2.47	4.5	not available	2.9	2.31	2.4	1.06	36	Varies
<b>Standard Color</b>	<b>Black</b>	Black/Gray	Black	Black	Black	Black	Black/ Green	Green	concrete	concrete
<b>Load Strength Empty</b>	<b>2,100 psi/ 5,721 psi Filled</b>	420 psi	685 psi	298 psi	6747 psi	365 psi	595 psi	299 psi	5000 psi +	3000 psi +
<b>Paver Flexibility</b>	<b>Flexible</b>	Rigid	Rigid	Rigid	Rigid	Flexible	Rigid	Rigid	Rigid	Rigid
<b>Soil Coverage at Surface - approx.</b>	<b>100%</b>	87%	98%	100%	100%	100%	93%	96%	70%	Not available
<b>Root Area at Base of Unit - approx.</b>	<b>92%</b>	41%	44%	90-95%	Not Available	Not Available	46%	16%	35%	40%
<b>Cutting Tools for Installation</b>	<b>Pruning Shears</b>	handsaw	handsaw	Saw	Not Specified	Hand Pruner	handsaw	handsaw	conc. saw	conc. saw
<b>Interlocking</b>	<b>Yes</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes
<b>Labor Skill Level Needed</b>	<b>Semi/Low</b>	Semi/low	Semi/low	Semi/Low	Semi/Low	Semi/Low	Semi/low	Semi/low	Skilled	Skilled
<b>Grass Installation Methods</b>	<b>All</b>	All	All	All	All	All	All	All	Seed	Seed
<b>Water Absorbtion (Freezing)</b>	<b>None</b>	None	None	None	None	None	None	None	Yes	Yes
<b>Oil Absorbtion/Retention</b>	<b>None</b>	None	None	None	None	None	None	None	Yes	Yes
<b>Affects from Turf Chemicals</b>	<b>None</b>	None	None	None	None	None	None	None	Minimal	Minimal
<b>Heat Absorbtion/Retention</b>	<b>None</b>	None	None	None	None	None	None	None	Moderate	Moderate
<b>Estimated Install Time per 1000 sqft</b>	<b>2 hr</b>	4.5 hrs +	4.5 hrs +	Unkown	Unkown	Unkown	4.5 hrs +	not available	not available	Varies

Grasspave2 -	le Structures, Inc., Aurora, Colorado 800-233-1510
Geoblock -	Presto Products, Inc., Appleton, WI
Grassroad Paver8 Plus (TM)	artron Corporation, Tempe, AZ (owned by NDS, Inc.)
Tuff Track -	NDS, Inc. Lindsay, CA
EcoRain-	EcoRain Systems, Inc. Sherman Oaks, CA
Airpave-	Airfield Systems, LLC. Edmond, OK
EZ Roll	NDS, Inc. Lindsay, CA
Grassy Pavers (TM)	RK Manufacturing, Inc., Jackson, MS
Grass-Cel -	Multi-Stream (Pte) Ltd. Singapore
Checker Block -	Hastings Pavement Co. Inc., Freeport, NY
Grasscrete -	Bomanite Corporation, Palo Alto, CA

\* - Grasspave2 is assembled and shipped into large rolls at the manufacturing plant. Rolls are made up of 40" x 40" x 1" interconnecting units. Chart entry b

\*\* - Grasscrete is a cast in place concrete system using plastic forms to create voids, which are later filled with soil and seeded.ased on standard model 2020 roll, other roll sizes available.

\*\*\* - Typical truck tire pressure (demand load) is 110 psi. Product filled per recommendations. Load capacity is variable depending upon base course strength, subsoil strength, and/or concrete mix strength.

\*\*\* - Typical truck tire pressure (demand load) is 110 psi. Product filled per recommendations. Load capacity is variable depending upon base course strength, subsoil strength, and/or concrete mix strength.

\*\*\* - Typical truck tire pressure (demand load) is 110 psi. Product filled per recommendations. Load capacity is variable depending upon base course strength, subsoil strength, and/or concrete mix strength.