

Sedimentation and Subsurface Water Storage Systems

When engineers and review authorities first encounter our Rainstore³ Subsurface Water Storage System, they will frequently ask how the storage chamber is maintained, especially for the removal of sediment. The structural nature of Rainstore³ is different from all other storage devices, employing a series of closely spaced, hollow, load-bearing columns. These columns make it impossible to physically enter the storage structure after installation is complete.

While sedimentation can be removed from these structures with the use of dedicated maintenance ports and submersible pumps, an even better solution is to avoid allowing sediment to even enter the structure.

What is the Source of Sediment?

The sediment we should be most concerned with is “suspended sediment”, generally defined as very fine soil (or other materials) particles that will stay in suspension even when water is moving slowly. Only when water is still (as within a storage structure) will these fine particles drop from suspension and settle to the bottom of the structure. The majority of these particles will pass a #200 screen and be classified as silt or clay sized particles.

Erosion by wind or water is the most common source of sediment materials, and is always a problem associated with construction sites. Solutions to reduce erosion impacts during construction are numerous, and beyond the scope of this paper. Current EPA regulations address erosion as a major water quality issue and do not need to be repeated here. All effort should be made to reduce the movement of soil by wind and water during construction, period.

Alternative 1 – Keep Sediment Out – Pre-filtration

Most Rainstore³ structures will be constructed during the early portions of site and building construction, while much of the site will remain exposed to erosion forces. During construction, stormwater must be kept clean and free from sediment before entry into the storage structure. If this is not possible, then provide a separate temporary detention/siltation basin and divert stormwater away from the storage structure.

At the completion of construction, permanent erosion control features (vegetation, ground cover and mulch, paving, etc.) should be in place and effective at minimizing sediment removal and transport. Long term sediment control measures may include both structural and non-structural approaches.

Structural sediment control measures include catch basin and inlet filtration, using geotextile filter bags, cyclonic water movement for deposition and control of debris and sediment (only partially effective with fine sediments), and sediment control structures (large concrete or plastic chambers allowing physical access).

Non-structural methods include vegetated slopes and swales, and bio-filtration inlets (sand filter with rapid water capture/conveyance below). An example might be the use of Grasspave² or Gravelpave² in a parking lot, with stormwater passing through the sand/gravel (filter) base course to Rainstore³ chambers below.

These techniques allow stormwater to be pre-filtered before entering the storage chambers. Maintenance (periodic removal of sediment captured) is kept to ground surfaces or easily accessible inlet structures.

Alternative 2 – Allow Sediment In

If sources of fine sediment can be identified and quantities generated can be estimated fairly accurately, then it is possible to allow suspended sediment laden stormwater to enter the storage structure. Thus, sediment volume can be controlled and either stored, or removed following capture.

Sediment Storage – if the volume of suspended sediment is anticipated to be quite small (relative to the overall storage volume), then plan for the additional storage volume of sediment in water storage calculations. If the Rainstore³ cells sit directly upon gravel, or a fabric layer above sand or gravel, the fine sediment material will pass through properly sized fabric and eventually fill the voids of gravel or sand layers below. The depth of the gravel or sand can be adjusted to occupy all or a majority of the historical sediment volume anticipated. Storage can also be accommodated within the Rainstore³ layers, by placing a controlled outlet pipe at a raised elevation off the floor of the storage structure.

Sediment Removal – if a more pro-active sediment control is desired, then placement of maintenance tubes, accessed from removable covers at the surface above the Rainstore³ storage chamber, will allow periodic flushing and/or pump removal of suspended sediments. Moving water will quickly put fine sediment back into suspension for removal by pump and/or outlet pipe (depending upon chamber size and geometry). Depending upon the source of sediment, possible hazardous contaminants (hydrocarbons, heavy metals, etc.) may require treatment or careful disposition of the sediment materials.

Conclusions

Sedimentation is basically an erosion control issue.

First choice – keep erosion from taking place.

Second choice – if erosion cannot be stopped, then control it by best means possible, keeping area of impact as small as possible.

Control stormwater speed (increase Time of Concentration), keeping speed as low as possible to minimize sediment particle size and volume.

Rough surfaces

Circuitous path

Shallow gradients

Use natural methods whenever possible to slow and filter stormwater before entering open drainages, creeks, rivers and oceans.

Porous paving, such as Grasspave² and Gravelpave².

Bio-slopes and Bio-swales, using Slopetame².

Bio-filters, using sand filters with Draincore² below.